



ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

Aluminium cable support and trunking systems

Meka Pro Oy



EPD HUB, HUB-7456

Published on 08.09.2026, last updated on 24.09.2026, valid until 07.09.2031

Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804, EPD Hub PCR version 1.2 (24 Mar 2025) and JRC characterization factors EF 3.1.



GENERAL INFORMATION

MANUFACTURER

Manufacturer	Meka Pro Oy
Address	Konetie 25, 90620 Oulu, Finland
Contact details	meka@meka.eu
Website	www.meka.eu

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804:2012+A2:2019/AC:2021 and ISO 14025
PCR	EPD Hub Core PCR Version 1.2, 24 Mar 2025
Sector	Construction product
Category of EPD	Third party verified EPD
Scope of the EPD	Cradle to gate with, A4-A5, and C1-C4, D
EPD author	Akseli Romppainen, LCA Point
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal verification ☒ External verification
EPD verifier	Elma Avdyli as an authorized verifier for EPD Hub

This EPD is intended for business-to-business and/or business-to-consumer communication. The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from

different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	Aluminium cable support and trunking systems
Place(s) of raw material origin	EU
Place of production	Oulu, Finland
Place(s) of installation and use	Finland
Period for data	Calendar Year 2024
Averaging in EPD	No grouping
Variation in GWP-fossil for A1-A3 (%)	-
A1-A3 Specific data (%)	99,3

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 kg of aluminium cable support and trunking systems
Declared unit mass	1 kg
Mass of packaging	0,03 kg
GWP-fossil, A1-A3 (kgCO ₂ e)	5,78
GWP-total, A1-A3 (kgCO ₂ e)	5,76
Secondary material, inputs (%)	47
Total energy use, A1-A3 (kWh)	30,3
Net freshwater use, A1-A3 (m ³)	2,74

PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

Meka Pro Oy is a Finnish family-owned business, which manufactures long life cycle cable management systems. The company has nine sales offices and a certified testing laboratory. It directly employs around 100 professionals. Meka now has employees in 6 countries and Meka has already delivered its products to its partners and customers in more than 80 countries. Fulfilling customer needs has always been a matter of honour for Meka. We keep, what we promise. This applies to both our products and our operations.

PRODUCT DESCRIPTION

Instal® cable trunking systems are certified in the Nordic countries. The system is easily adaptable and fit to any space. The clean-lined components and streamlined design make the system safe and quick to install. Instal® cable trunkings are also suitable for use in damp premises and can be used for heat, liquid and gas piping where appropriate. All Instal® cable trunking systems meet the related safety requirements.

Further information can be found at:
www.meka.eu

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass %	Material origin
Metals	100	EU
Minerals	-	-
Fossil materials	-	-
Bio-based materials	-	-

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	0,012

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 kg
Mass per declared unit	1 kg
Functional unit	-
Reference service life	25 years

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system boundaries	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	X	X	ND	ND	ND	ND	ND	ND	ND	X	X	X	X	X	
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction/ demolition	Transport	Waste processing	Disposal	Reuse	Recovery
																	Recycling

Not declared = ND.

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

A market-based approach is used in modelling the electricity mix utilized in the factory.

Aluminium profiles arrive at the manufacturing facility by road freight. The profiles are cut and shaped to achieve the required end product. All processing operations are carried out using electrically powered tools and equipment. Energy consumption has been accounted for in the LCA model.

Internal material handling within the facility is performed using diesel-powered forklift trucks, the fuel consumption of which has also been included in the model.

Approximately 2% of material is lost as production waste during the manufacturing process. This waste is directed to recycling. Finished products are packed onto pallets and protected with polyethylene film.

TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

Finished products are transported to customers by road freight, with an average delivery distance of 585 km, accounted for in module A4. Installation is carried out using handheld electrical tools, for which an electricity consumption of 0.01 kWh per declared unit has been allocated. Packaging waste is assumed to be mostly directed to recycling.


PRODUCT END OF LIFE (C1-C4, D)

Disassembly is assumed to consume 0.01 kWh per kilogram of product, with the same handheld power tools assumed as for installation. Transportation to waste treatment facilities is assumed to occur by lorry over an average distance of 50 km (C2). Approximately 90% of the aluminium content is assumed to be recycled (C3), with the remaining 10% directed to landfill for

final disposal (C4) (Eurostat 2020). The net benefits arising from recycling have been accounted for in module D.

EPD Hub - EPD Central Data Repository

MANUFACTURING PROCESS & SYSTEM DIAGRAM



LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

VALIDATION OF DATA

Data collection for production, transport, and packaging was conducted using time and site-specific information, as defined in the general information section on page 1 and 2. Upstream process calculations rely on generic data as defined in the Bibliography section. Manufacturer-provided specific and generic data were used for the product's manufacturing stage. The analysis was performed in One Click LCA EPD Generator, with the 'Cut-Off, EN 15804+A2' allocation method, and characterization factors according to EN 15804:2012+A2:2019/AC:2021 and JRC EF 3.1.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging material	Not applicable
Ancillary materials	Not applicable
Manufacturing energy and waste	Physical Properties

PRODUCT & MANUFACTURING SITES GROUPING

Type of grouping	No grouping
Grouping method	Not applicable
Variation in GWP-fossil for A1-A3, %	-

This EPD is product and factory specific.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator for EPD Hub V3 and EPD Process Certification v3.2.5. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.10.1/3.11/3.12 and One Click LCA databases as sources of environmental data. Allocation used in Ecoinvent 3.10.1/3.11/3.12 environmental data sources follow the methodology 'allocation, Cut-off, EN 15804+A2'.

ENVIRONMENTAL IMPACT DATA

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	5,47E+00	1,84E-01	1,09E-01	5,76E+00	6,26E-02	3,85E-02	ND	ND	ND	ND	ND	ND	ND	1,56E-03	2,48E-02	2,44E-02	1,67E-03	-6,02E+00
GWP – fossil	kg CO ₂ e	5,45E+00	1,84E-01	1,46E-01	5,78E+00	6,25E-02	1,98E-03	ND	ND	ND	ND	ND	ND	ND	1,52E-03	2,48E-02	2,45E-02	1,67E-03	-5,86E+00
GWP – biogenic	kg CO ₂ e	1,51E-02	4,18E-05	-3,65E-02	-2,14E-02	1,44E-05	3,65E-02	ND	ND	ND	ND	ND	ND	ND	1,98E-05	5,61E-06	-7,31E-05	6,82E-06	-1,00E-02
GWP – LULUC	kg CO ₂ e	1,88E-03	8,15E-05	1,08E-04	2,07E-03	2,79E-05	2,49E-05	ND	ND	ND	ND	ND	ND	ND	2,47E-05	1,11E-05	2,88E-05	1,83E-06	-1,49E-01
Ozone depletion pot.	kg CFC-11e	1,98E-07	2,69E-09	2,65E-09	2,04E-07	9,09E-10	2,27E-11	ND	ND	ND	ND	ND	ND	ND	1,99E-11	3,65E-10	2,63E-10	3,45E-11	-1,06E-07
Acidification potential	mol H ⁺ e	3,33E-02	6,35E-04	8,46E-04	3,48E-02	2,17E-04	1,00E-05	ND	ND	ND	ND	ND	ND	ND	9,05E-06	8,44E-05	2,62E-04	1,04E-05	-3,86E-02
EP-freshwater ²⁾	kg Pe	1,06E-03	1,98E-05	8,79E-05	1,17E-03	6,78E-06	8,21E-07	ND	ND	ND	ND	ND	ND	ND	7,74E-07	1,93E-06	1,32E-05	2,38E-07	-3,36E-03
EP-marine	kg Ne	5,00E-03	2,10E-04	1,54E-04	5,36E-03	7,19E-05	2,13E-06	ND	ND	ND	ND	ND	ND	ND	1,64E-06	2,77E-05	5,81E-05	4,28E-06	-5,25E-03
EP-terrestrial	mol Ne	4,83E-02	2,27E-03	1,54E-03	5,21E-02	7,77E-04	2,12E-05	ND	ND	ND	ND	ND	ND	ND	1,79E-05	3,02E-04	6,55E-04	4,13E-05	-4,76E-02
POCP (“smog”) ³⁾	kg NMVOCe	1,54E-02	9,32E-04	5,28E-04	1,68E-02	3,19E-04	5,77E-06	ND	ND	ND	ND	ND	ND	ND	4,61E-06	1,24E-04	1,93E-04	1,37E-05	-2,09E-02
ADP-minerals & metals ⁴⁾	kg Sbe	1,32E-05	5,27E-07	2,46E-06	1,61E-05	1,79E-07	4,32E-08	ND	ND	ND	ND	ND	ND	ND	4,17E-08	6,91E-08	1,44E-06	3,76E-09	-1,18E-05
ADP-fossil resources	MJ	6,84E+01	2,62E+00	3,05E+00	7,40E+01	8,92E-01	7,11E-02	ND	ND	ND	ND	ND	ND	ND	6,82E-02	3,59E-01	2,89E-01	3,18E-02	-9,25E+01
Water use ⁵⁾	m ³ e depr.	1,11E+00	1,53E-02	3,87E-02	1,16E+00	5,21E-03	1,72E-03	ND	ND	ND	ND	ND	ND	ND	1,67E-03	1,77E-03	4,57E-03	1,45E-03	-1,22E+01

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	0,00E+00	1,79E-08	8,34E-09	2,63E-08	6,13E-09	8,30E-11	ND	ND	ND	ND	ND	ND	ND	6,17E-11	2,48E-09	3,65E-09	2,13E-10	-4,36E-07
Ionizing radiation ⁶⁾	kBq 11235a	0,00E+00	2,21E-03	1,43E-01	1,45E-01	7,48E-04	3,98E-03	ND	ND	ND	ND	ND	ND	ND	3,97E-03	3,13E-04	1,04E-03	4,72E-05	-1,58E+00
Ecotoxicity (freshwater)	CTUe	0,00E+00	5,66E-01	3,97E+00	4,54E+00	1,85E-01	8,58E-03	ND	ND	ND	ND	ND	ND	ND	7,10E-03	5,08E-02	1,68E-01	8,98E+02	-1,57E+02
Human toxicity, cancer	CTUh	0,00E+00	2,89E-11	1,10E-10	1,39E-10	9,82E-12	9,09E-13	ND	ND	ND	ND	ND	ND	ND	7,41E-13	4,09E-12	1,96E-11	9,21E-13	-1,07E-08
Human tox. non-cancer	CTUh	0,00E+00	1,63E-09	2,72E-09	4,35E-09	5,55E-10	4,57E-11	ND	ND	ND	ND	ND	ND	ND	4,20E-11	2,33E-10	1,25E-09	1,75E-10	-7,20E-08
SQP ⁷⁾	-	0,00E+00	2,60E+00	4,38E+00	6,98E+00	8,90E-01	3,11E-02	ND	ND	ND	ND	ND	ND	ND	2,73E-02	3,62E-01	5,47E-01	6,10E-02	-4,90E+00

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	2,63E+01	3,65E-02	5,34E-01	2,68E+01	1,24E-02	2,43E-02	ND	ND	ND	ND	ND	ND	ND	2,42E-02	4,92E-03	4,49E-02	7,14E-04	-3,83E+01
Renew. PER as material	MJ	0,00E+00	0,00E+00	3,63E-01	3,63E-01	0,00E+00	-3,63E-01	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	9,70E-02
Total use of renew. PER	MJ	2,63E+01	3,65E-02	8,97E-01	2,72E+01	1,24E-02	-3,39E-01	ND	ND	ND	ND	ND	ND	ND	2,42E-02	4,92E-03	4,49E-02	7,14E-04	-3,83E+01
Non-re. PER as energy	MJ	7,68E+01	2,62E+00	2,92E+00	8,23E+01	8,92E-01	-1,35E-02	ND	ND	ND	ND	ND	ND	ND	6,82E-02	3,59E-01	2,89E-01	3,18E-02	-9,25E+01
Non-re. PER as material	MJ	0,00E+00	0,00E+00	1,09E-01	1,09E-01	0,00E+00	-1,09E-01	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,80E-02
Total use of non-re. PER	MJ	7,68E+01	2,62E+00	3,03E+00	8,24E+01	8,92E-01	-1,22E-01	ND	ND	ND	ND	ND	ND	ND	6,82E-02	3,59E-01	2,89E-01	3,18E-02	-9,25E+01
Secondary materials	kg	4,70E-01	1,10E-03	2,34E-03	4,74E-01	3,74E-04	1,76E-05	ND	ND	ND	ND	ND	ND	ND	1,05E-05	1,53E-04	3,34E-04	1,17E-05	1,00E+00
Renew. secondary fuels	MJ	0,00E+00	1,43E-05	1,23E-02	1,23E-02	4,87E-06	1,10E-07	ND	ND	ND	ND	ND	ND	ND	4,80E-08	1,94E-06	1,52E-05	1,99E-07	-1,81E-04
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of net fresh water	m ³	2,74E+00	3,75E-04	3,29E-03	2,74E+00	1,28E-04	3,96E-05	ND	ND	ND	ND	ND	ND	ND	3,90E-05	5,31E-05	1,26E-04	-3,76E-04	-2,63E-01

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	2,84E-01	1,66E-02	7,76E-03	3,08E-01	5,71E-03	1,22E-03	ND	ND	ND	ND	ND	ND	ND	1,19E-03	6,09E-04	2,25E-03	1,58E-04	-1,28E+00
Non-hazardous waste	kg	1,32E+00	3,28E-01	2,43E-01	1,89E+00	1,13E-01	5,32E-03	ND	ND	ND	ND	ND	ND	ND	4,19E-03	1,13E-02	6,34E-02	2,85E-01	-1,56E+01
Radioactive waste	kg	5,04E-03	5,29E-07	5,24E-06	5,04E-03	1,79E-07	8,55E-07	ND	ND	ND	ND	ND	ND	ND	8,52E-07	7,66E-08	2,55E-07	1,15E-08	-4,20E-04

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	3,38E-01	0,00E+00	0,00E+00	3,38E-01	0,00E+00	2,40E-02	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	0,00E+00	0,00E+00	2,00E-02	2,00E-02	0,00E+00	1,90E-03	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	9,00E-01	0,00E+00	0,00E+00
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy – Electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy – Heat	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO ₂ e	5,45E+00	1,84E-01	1,46E-01	5,78E+00	6,26E-02	2,01E-03	ND	ND	ND	ND	ND	ND	ND	1,54E-03	2,48E-02	2,45E-02	1,67E-03	-6,01E+00

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows – CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide – were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterisation factor for biogenic CO₂ is set to zero

SCENARIO DOCUMENTATION

DATA SOURCES

Manufacturing energy scenario documentation

1. Electricity, residual mix , Finland, BAFU, 0.38 kgCO₂e/kWh
2. Market for heat, district or industrial, other than natural gas, Ecoinvent, 0.0715 kgCO₂e/MJ
3. Diesel, burned in building machine, World, Ecoinvent, 0.10 kgCO₂e/MJ

Transport scenario documentation - A4 (Transport resources)

1. Market for transport, freight, lorry, >32 metric ton, diesel, EURO 5, 550.0 km

Transport to the building site (A4) - Scenario documentation

Scenario parameter	Value
Capacity utilization (including empty return) %	100
Bulk density of transported products	1,03
Volume capacity utilization factor	1

Installation at the building site (A5) - Scenario documentation

Scenario parameter	Value
Energy: type and consumption (MJ or kWh)	Electricity low voltage, 0.01 kWh/DU, via handheld screwdriver
Water use (m ³)	-
Ancillary materials: type and mass (kg)	-
Waste materials: type and mass (kg)	PE 0,002 kg Wood 0,024 kg
Waste materials: output routes	PE for recycling 95% PE for landfill 5% Wood for recycling 100%
Direct emissions (kg)	-

End of life (C1-C4) - Scenario documentation

Scenario information	Value
Collection process: collected separately (kg)	1
Collection process: Mixed waste (kg)	-
Recovery: re-use (kg)	0
Recovery: recycling (kg)	0,9
Recovery: energy recovery (kg)	0
Disposal (kg)	0,1
Scenario assumptions e.g. transportation (mode, km) & other	Truck 50 km

THIRD-PARTY VERIFICATION STATEMENT

EPD Hub declares that this EPD is verified in accordance with ISO 14025 by an independent, third-party verifier. The project report on the Life Cycle Assessment and the report(s) on features of environmental relevance are filed at EPD Hub. EPD Hub PCR and ECO Platform verification checklist are used.

EPD Hub is not able to identify any unjustified deviations from the PCR and EN 15804+A2 in the Environmental Product Declaration and its project report.

EPD Hub maintains its independence as a third-party body; it was not involved in the execution of the LCA or in the development of the declaration and has no conflicts of interest regarding this verification.

The company-specific data and upstream and downstream data have been examined as regards plausibility and consistency. The publisher is responsible for ensuring the factual integrity and legal compliance of this declaration.

The software used in creation of this LCA and EPD is verified by EPD Hub to conform to the procedural and methodological requirements outlined in ISO 14025:2010, ISO 14040/14044, EN 15804+A2, and EPD Hub Core Product Category Rules and General Program Instructions.

Verified tools

Tool verifier: Magaly Gonzalez Vazquez

Tool verification validity: 27 March 2025 - 26 March 2028

Elma Avdyli as an authorized verifier for EPD Hub Limited 08.09.2026

