

CERTIFICATE OF CONFORMITY

Cable type: **GAALFLEX SERVO T 834 C**

We confirm that the above mentioned cable is produced according to:

Conductor construction acc. to IEC 60228, DIN VDE 0295
Color cores acc. to EN 50334;
Outer sheath orange RAL 2003;
Flame retardant acc. to IEC EN 60332-1-2, UL CSA FT-1/-2
Oil resistant acc. to IEC 60811-2-1, DIN VDE 0473 part.811-2-1;
Halogen free acc. to IEC 60754-1, DIN VDE 0472 part. 15
UL Style 21223 80°C 1000 V

Temperature range:

-Fixed installation: -50°C up to +90°C
-Flexible installation: -40°C up to +90°C
UL: up to +80°C

Temperature at conductor:

-in service: +90°C
-in short-circuit: +250°C



Nominal voltage:

-U₀/U: 0,6/1 kV **UL: 1000 V**

acc. to RoHS-guideline 2002/95/EG as well as GefStoffV appendix IV-no. 24
CE: The product is conformed with the EC Low-Voltage Directive 2006/95/EC

WARRANTY PERIOD:

The warranty period is 24 months after delivery

Operator	Technical manager
 - Andrea Fiorini	 Luca Bolondi