# TECHNICAL DATASHEET

CleanAIR®

www.**clean-air**.cz

## Light flexi hose QuickLOCK™ - CA40x1/7"
Light flexi hose with QuickLOCK™ locking system.



* the picture is illustrational only and may vary depending on additional equipment

### Description

Light flexi hose with QuickLOCK™ - CA40x1/7"
connectors.

### Application

For a connection between the CleanAIR® PAPR and full
range of CleanAIR® headtops except of full face masks.

DA-090_-_710060_-_Light_flexi_hose_QuickLOCK_-_CA40x17_-_EN

**Malina Safety®**

**MALINA - Safety s.r.o.**
Luční 11, 466 01 Jablonec n. Nisou, Czech Republic
Tel.: +420 483 356 600, Email.: export@malina-safety.cz
Web.: www.malina-safety.cz / www.clean-air.cz

Revision.: 2021_05_28
Output.: 2021_05_28

# TECHNICAL DATASHEET

## *Light flexi hose QuickLOCK™ - CA40x1/7"*
Light flexi hose with QuickLOCK™ locking system.

### *Technical specification*

| | |
|---|---|
| Product code | 71 00 60 |
| Weight | 240 g |
| Dimensions | length: 600 mm (in relaxed state), diameter: 50 mm |
| Materials | connectors - ABS<br>main hose - PUR, PC+ABS |
| Storage conditions<br>Operating conditions | – 10°C to + 55°C, humidity 0 - 95 % Rh<br>   0°C to + 60°C, humidity 20 - 95 % Rh |