

# Declaration of Performance

## T4308OPCPR

1. Unique identification code of the product-type:

Thermo-teK LM Air ALU

2. Intended use or uses:

Thermal Insulation products for building equipment and industrial installations

3. Manufacturer:

Knauf Insulation s.r.o.  
Železničný rad 24, 968 14 Nová Baňa  
Slovakia  
www.knaufinsulation.com - dop@knaufinsulation.com

4. Authorised representative:

Not applicable

5. System or systems of assessment and verification of constancy of performance:

AVCP System 1 for Reaction to Fire  
AVCP System 3 Internal measurements for mechanical and thermal properties

6a. Harmonized Standard:

EN 14303:2009 + A1:2013

Notified body or bodies:

AVCP System 1: (Notified certification body) 1301 - Technický a skusobný ústav stavebný, n. o. - - -

6b. European Assessment document: not applicable

European Technical Assessment: not applicable

Technical Assessment Body: not applicable

Notified body/ies: not applicable

7. Declared Performances:

See next page

Essential Characteristics	T4308OPCPR			Harmonised Technical Standard
	Performance		Thermo-teK LM Air ALU	
Reaction to fire	Reaction to fire		A2-s1,d0	EN 14303:2009 + A1:2013
Acoustic Absorption Index	Sound Absorption		NPD	
Water Permeability	Water Absorption		NPD	
Water Vapour Permeability	Water Vapour Diffusion Resistance		NPD	
Compressive Strength	Compressive Stress or Compressive Strength for Flat Products		NPD	
Rate of release of corrosive substances	Trace quantities of water-soluble ions and the pH-value		NPD	
Release of Dangerous Substances to the indoor environment	Release of Dangerous Substances		NPD	
Continuous glowing combustion	Continuous glowing combustion		NPD	
Durability of reaction to fire against ageing / degradation	Durability characteristics		NPD {b}	
Durability of thermal resistance against ageing/degradation	Thermal Conductivity		NPD {c}	
	Dimensional Stability		NPD	
	Maximum service temperature - dimensional stability		NPD	
	Durability characteristics		NPD	
Durability of reaction to fire against high temperature	Durability characteristics		NPD {d}	
Durability of thermal resistance against high temperature	Durability Characteristics		NPD {c}	
	Maximum service temperature - dimensional stability		NPD	
Thermal Resistance	Dimensions & Tolerances		25 - 100   T5	
	Thermal conductivity (W/mk) at Temperature in °C	10	0,036	
		50	0,044	
		100	0,055	
		150	0,072	
		200	0,088	
		250	0,112	
		NPD	NPD	
		NPD	NPD	
		NPD	NPD	
NPD - No performance determined				

8. Appropriate Technical Documentation and / or Specific Technical Documentation:

Not applicable

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for an on behalf of the manufacturer by:

Marián Tkáč - Plant manager

(Name and function)



Nova Bana - 09-12-19

(Place and date of issue)

Footnotes

{a} The requirement on a certain characteristic is not applicable in those Member States (MSs) where there are no regulatory requirements on that characteristic for the intended use of the product. In this case, manufacturers placing their products on the market of these MSs are not obliged to determine nor declare the performance of their products with regard to this characteristic and the option 'No performance determined' (NPD) in the information accompanying the CE marking (see ZS.3) may be used. The NPD option may not be used, however, where the characteristic is subject to a threshold level (thermal resistance (thermal conductivity and thickness)).

{b} The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic contents, which cannot increase with time.

{c} Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.

{d} The fire performance of mineral wool does not deteriorate with high temperature. The Euroclass classification of the product is related to the organic content, which remains constant or decreases with high temperature.