

Ekoflock 50-100

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: Ekoflock 50-100

Registration number reach: 01-2119531563-43 **Product type REACH:** Substance/UVCB

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Water treatment in industrial and professional use

Industrial formulation and (re)packing

For more detailed information regarding the Identified Uses, see Exposure Scenarios

Uses advised against. No uses advised against known.

1.3 Details of the supplier of the safety data sheet

Supplier: Feralco Nordic AB

Lilleviksvägen

294 35 Sölvesborg SWEDEN

 Tel:
 +46 (0)456-156 16

 Fax:
 +46 (0)456-199 35

 E-mail:
 info.se@feralco.com

1.4 Emergency telephone number

Emergency telephone 020-996 000 (sweden)

number: +46(0) 8 33 70 43 (international)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards: Met. Corr.1 H290 – May be corrosive to metals

Health Hazards: Eye Dam.1 H318 – Causes serious eye damage

2.2 Label elements

Label according to Regulation (EC) No 1272/2008 as amended.

Hazard pictograms

Signal Word: Danger

Hazardous substances which must be listed on the label

CAS-No Substance

1327-41-9 Polyaluminium chloride

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

Hazard statements

H290 May be corrosive to metals. H318 Causes serious eye damage.

Precautionary statements

P280 Wear eye protection.

P305 +P351 + P338 IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P406 Store in corrosion-resistant container or in container with a resistant inner liner.

2.3 Other hazards

Other hazardous properties: May cause lowering of pH in watercourses and can thus be dangerous for aquatic

organisms.

Contact with non-precious metals (e.g iron, zinc and aluminium) and their alloys

Eye. Dam.1;H318

generates hydrogen gas, which can form an explosive mixture with air.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Hazardous substances % EC-/CAS-No Classification REACH reg.No EU 1272/2008

1.Polyaluminium chloride 18-43 215-477-2 Met. Corr. 1;H290

1327-41-9 01-2119531563-43

Additional information: See section 16 - OTHER INFORMATION for the text of H-phrases mentioned in this

section.

4. FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation: Move the injured to fresh air upon irritation or breathing difficulty.

Call a physician if symptoms develop or persist.

Skin contact: Rinse skin with plenty of water. Get medical attention if irritation persists.

Eye contact: Immediately flush eyes with plenty of water for several minutes, keep eyelids wide open.

Remove contact lenses if present and easy to do. Continue rinsing. Seek medical

attention.

Ingestion: Rinse mouth with water and then drink much water. If ingestion of a large amount does

occur, call a poison control center or a doctor immediately.

Notes to medical staff: Treat symptomatically. Show this safety data sheet.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: Corrosive damage to eye tissue which can cause serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Treat symptomatically.

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

5. FIRE FIGHTING MEASURES

General fire hazards: Not a fire hazard. Noncombustible substance.

5.1 Extinguishing media

Extinguishing media: Determined by surrounding material/products present.

Unsuitable extinguishing

media:

Non known

5.2 Special hazards arising from the substance or mixture

Special exposure hazards: Small amounts of hydrochloric acid fumes may be emitted during thermal decomposition.

5.3 Advice for firefighters

Special protective equipment: Use self-contained breathing apparatus and protective clothing. Exposure to

decomposition products may be harmful.

Further information: Collect contaminated fire extinguishing water separately. This must not be discharged

into drains.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

See reference below 6.4.

If discharged to soil or water contact local authorities/emergency services. Keep unauthorized personnel away. Do not touch spillage of the material and do not walk through it.

6.2 Environmental precautions

Prevent further leakage or spillage. Do not flush into surface water or sanitary sewer system. Avoid discharge into drains, watercourses, or on the ground and in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Contain and adsorb spillages with materials like vermiculite, sand, earth or other inert material. Place into a container for later disposal. Following product recovery, flush area with water. Never return spills to original containers for re-use.

6.4 Reference to other sections

Personal precautions: See Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Waste disposal: See Section 13 – DISPOSAL CONSIDERATIONS

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Handling: Workplace and working procedures shall be designed to prevent or minimize direct

contact with the product. Do not get this material in contact with eyes. Provide adequate ventilation. Avoid spills and prevent the product from reaching drains. For personal protection see Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

7.2 Conditions for safe storage, including any incompatibilities

Store in original packaging or in a container/tank of plastic (PE, PP, PVC) glass fiber Storage:

reinforced polyester (FRP) or steel with rubber lining.

Materials to avoid: Avoid most metals, especially the non-precious variety. Oxidizing agents, reducing

agents.

7.3 Specific end use(s)

No information available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational exposure limits: SE: NGV Aluminium, soluble compound (As Al) total dust 1 mg/m^3

Time-weighted average exposure limit 8 h

Aluminium salts, soluble. Time-weighted average exposure UK: 2 mg/m^3

limit 8 h (Workplace exposure limit (EH40/2005))

DNEL/DMEL- Workers, aluminium chloride basic (CAS 1327-41-9)

Effect level (DNEL/DMEL	Type	Value
DNEL	Long-term systemic effects inhalation	16.4 mg/m ³
	Long-term systemic effects dermal	4.6 mg/kg bw/day

DNEL/DMEL - general population, aluminium chloride, basic (CAS 1327-41-9)

Effect level	Type	Value
DNEL	Long term systemic effects inhalation	4 mg/m³
DMEL	Long term systemic effects dermal	2.32 mg/kg bw/day
DNEL	Long term systemic effects oral	2.3 mg/kg bw/day

PNEC - aluminium chloride . basic (CAS 1327-41-9)

Compartments	Value
Fresh water	0,3 μg/l
Marine water	0,03 µg/l
STP	20 mg/l

8.2 Exposure controls

For more detailed information regarding the Identified Uses, see Exposure Scenarios. The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

Appropriate engineering

controls:

Provide adequate ventilation in the work area.

Eye protection: Safety goggles with side shields. Eyewash station shall be accessible.

Hand protection: Protective gloves against chemicals (EN 374).

Suitable material: PVC, neoprene rubber, nitrile rubber, butyl rubber.

Skin protection: Protective clothing is recommended. Wash contaminated clothing before reuse.

Not applicable under normal operating conditions. At formation of aerosols or vapour use Respiratory protection:

half face mask respirators with particle filter P2.

Environmental exposure

controls:

Avoid release to the environment. Authorities concerned must be informed of

releases.

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state: Liquid

Colour: Colourless to yellow Odour: Slight odour Odour threshold: No data available

pH: < 2 value using conventional measurement methods

(special method is required for the correct value when pH > 2 is obtained see 9.2 other information)

Meltingpoint/freezing point: - 18°C - -75°C Boiling point, initial boiling 105°C - 115°C

point, and boiling range:

Flashpoint:

Evaporation rate:

Flammability (solid, gas):

Flammability limit or

Not applicable
No data available
Not combustible
No data available

explosive limit:

Vapour pressure:No data availableVapour density:No data availableRelative density:1,2 - 1,4 ; 20°CSolubility (water):MisciblePartition coefficientNot applicable

(n-octanol/water):

Auto-ignition temperature: Not applicable **Decomposition temperature:** > 200°C

Viscosity: 10-50 mPa.s (20 °C)

9.2 Other information

Because of its high ionic strength and composition, the product cannot be analyzed by standard analytical methods for water. Especially developed and adapted methods are required. When calculating the pH, >2 pH < 4 is obtained. Polyaluminium chloride = aluminium chloride, basic = aluminium hydroxy chloride.

Density: $1200 - 1400 \text{ kg/m}^3$

10. STABILITY AND REACTIVITY

10.1 Reactivity

Reacts with most metals, especially base metals and their alloys.

10.2 Chemical stability

The product is stable under normal conditions.

10.3 Possibility of hazardous reactions

Contact with non-precious metals (e.g. iron, zinc and aluminium) and their alloys generates hydrogen gas, which can form an explosive mixture with air.

10.4 Conditions to avoid

None under normal conditions. Do not expose to temperatures above 50° C. Thermal decomposition can take place above 200° C.

10.5 Incompatible materials

This product may react with strong reducing agents and strong oxidizers.

10.6 Hazardous decomposition products

ISSUE DATE: 2020-01-24

Version: 4 (Replaces version 3)

n: 4 page 5 of 11



Ekoflock 50-100

No dangerous reactions known under condition of normal use. Thermal decomposition can lead to release of irritating gases and vapors. Hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Ekoflock 50-100 No test data available, aluminium chloride, basic (CAS 1327-41-9)

alaminan c	nonac, basic (0/10/10/27 41 3	"				
Route of	Parameter	Method	Value	Exposure	Species	Value	Remark
exposure				time		determination	
Oral	LD50	OECD 401	> 2000		Rat	Experimental	Aqueous
			mg/kg bw		(male/female)	value	solution
Dermal	LD50	OECD 402	> 2000	24 h	Rat	Experimental	Aqueous
			mg/kg bw		(male/female)	value	solution
Inhalation	LC50	OECD 403	> 5mg/l	4 h	Rat	Read-across	Aqueous
(aerosol)			-		(male/female)		solution

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Ekoflock 50-100 No test data available, aluminium chloride, basic (CAS 1327-41-9)

<u> </u>		<u> </u>	• /				
Route of	Result	Method	Exposure	Time point	Species	Value	Remark
exposure			time			determination	
Eye	Serious eye damage	OECD 405	21 days	24; 48; 72 hours	Rabbit	Experimental value	Aqueous solution
Skin	Not irritating	OECD 404	4 h	24; 48; 72 thours	Rabitt	Experimental value	Aqueous

Conclusion

Causes serious eye damage.

Not classified as irritating to the respiratory system

Not classified as irritating to the skin

Respiratory or skin sensitisation

Ekoflock 50-100 No test data available.

aluminium chloride, basic (CAS 1327-41-9)

<u>alaminam o</u>	monac, bacic (0,10 10=, 11 0	"				
Route of	Result	Method	Exposure	Observation	Species	Value	Remark
exposure			time	time point		determination	
Skin	Not	OECD 406			Guinea pig	Experimental	Aqueous
	sesitizing				(female)	value	solution

Conclusion

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin

Specific target organ toxicity

Ekoflock 50-100 No test data available,

aluminium chloride, basic (CAS 1327-41-9)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL systemic effects	OECD 422	1000 mg/kg bw/dag		No adverse systemic effecs	28 days – 53 days	Rat (male/ female)	Experimental value
Dermal								Data waiving
Inhalation (aerosol)	LOAEC	Equivalent to OECD 413	15,3 mg/m³ air	Lungor	Lung tissue affection/ degeneration	13 weeks(6 h/day, 5 days/week)	Rat (male/ female	Read-across

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

<u>Conclusio</u>n

Not classified for subchronic toxicity

Mutagenicity (in vitro)

Ekoflock 50-100 No test data available, aluminium chloride. basic (CAS 1327-41-9)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium)		Experimental value	Aqueous solution
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y-cells)		Experimental value	Aqueous solution

Mutagenicity (in vivo)

Ekoflock 50-100 No test data available, aluminium chloride, basic (CAS 1327-41-9)

Result Method Exposure time Test substrate Organ Value determination **OECD 474** Negative (oral 2 doses/24 hour Rat (male/ Experimentel (stomach tube)) interval female value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

Ekoflock 50-100 No test data available, aluminium chloride, basic (CAS 1327-41-9)

Route of	Parameter	Method	Value	Exposure	Species	Effect	Organ	Value
exposure				time				determination
Oral (drinking water)	NOAEL	Cancerogenic toxicity study	5 ppm		Mouse (male/female)	No carcinogenic effect		Read-across

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

Ekoflock 50-100 No test data available, aluminium chloride, basic (CAS 1327-41-9)

	Parameter	Metod	Värde	Exponeringstid	Art	Effekt	Organ	Bestämning av värde
Developmental toxicity (Oral(drinking water))	NOAEL	Equivalent to OECD 426	3225 mg/kg bw/dag	1 year	Rat	No effect		Read-across
Effects on fertiliteten (Oral (stomach tube))	NOAEL	OECD 422	1000 mg/kg bw/dag	4 weeks (7 days/week)	Rat (male/female)	No effekt		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

Ekoflock 50-100 No test data available

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

Chronic effects from short and long-term exposure

Ekoflock 50-100 No effects known

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Ekoflock 50-100 No test data available aluminium chloride, basic (CAS 1327-41-9).

	Para- meter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	186 mg/l	96 h	Danio rerio	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	98 mg/l	48 h	Daphnia magna	Semi- static system	Fresh water	Experimental value; Nominal concentration
Long term toxicity aquatic crustacea	NOEC	EPA 600/4- 89/001	3,8 mg/l	8 days	Ceriodaphnia dubia	Semi static system	Fresh water	Experimental value; Nominal concentration
Toxicity aquatic micro organisms	EC50	OECD 209	> 1000 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimentel value of a similar product; GLP

Judgement of the mixture is based on the relevant ingredients

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2 Persistence and degradability:

The product solely consists of inorganic compounds which are not biodegradable.

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential:

Not applicable.

12.4 Mobility in soil:

No (test)data on mobility of the substance available

12.5 Results of PBT and vPvB assessment:

Not applicable. Inorganic substance.

12.6 Other adverse effects:

The pH-lowering capacity can be dangerous and obstructive to aquatic organisms. The amount of algae is significantly reduced at pH <6. In the pH-range of about 5-5,5 aluminium ions can be harmful to the salmonids. Aluminium salts should not enter water in an uncontrolled manner and pH fluctuations around 5-5,5 should be avoided. Around neutral pH, aluminium salts are not harmful to fish.

Do not discharge into drains, water courses or onto the ground.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

13. DISPOSAL CONSIDERATIONS

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

13.1 Waste treatment methods

Product waste: Classified as hazardous waste. Dispose of in accordance with current regulations (local,

regional, national, international). Get advice from local authorities.

Packaging waste: Dispose of in accordance with current regulations (local, regional, national, international).

Get advice from local authorities. Before leaving plastic packages for recycling its recommended to remove product residues by rinsing the emptied package with water three times. If possible reuse the rinse water in the process where the product is used. Set the package upside down for runoff. Left with cap removed. If package is emptied but not

cleaned, warnings according to label must be followed.

Disposal methods/ information Do not contaminate soil or water. Do not dispose of product to sewer.

Waste code, according to waste regulations, should be assigned by the user based on the

application for which the product was used. The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

14. TRANSPORT INFORMATION

14.1 UN number:

UN number 3264

14.2 UN Proper shipping name

Proper shipping name: CORROSIVE LIQUID, ACIDIC INORGANIC, N.O.S (Polyaluminium chloride solution)

Regulations	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Marine pollutant	Tunnel restriction code
ADR/RID	8; code C1	III	No	(E)
IMDG	8; EmS: F-A, S-B	III	No	-
IATA/ICAO (Flyg)	·,· · ·, · -	III	No	-
ADN	8	III	No	-
		No.		No. of the last of
		8		

Hazard code No **80** (ERG code 8L)
Passenger and
cargo aircraft:
Cargo aircraft only:

Allowed

Limited quantities: Combination packagings: not more than 5 liters per inner packaging for

liquids. A package shall not weigh more than 30 kg. (gross mass)

14.6 Special precautions for user

No information available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available.

ISSUE DATE: 2020-01-24

Version: 4



Fkoflock 50-100

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations: Young people under 18 years old are not allowed to work with this product according to

EU Directive 94/33/EC on the protection of young people at work.

European drinking water standards (Directive 98/83/EC)

Ekoflock 50-100

=				
	Parameter	Parametervärde	Anmärkning	Referens
	Chloride	250 mg/l		Listed in Annex I, Part C, of Directive 98/83/EC on the quality of water intended for human consumption.
				water interface for namen consumption.

Otherwise not included in regulations that have not been previously provided in the safety data sheet.

15.2 Chemical safety assessment

Chemical A chemical safety assessment has been carried out as a part of the REACH-

safety assessment: registration dossier.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)* Australia Australian Inventory of Chemical Substances (AICS) Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes Europe European Inventory of New and Existing Chemicals (EINECS) Yes Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) Yes Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes Philippines Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS) United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. OTHER INFORMATION

Revision information: The safety data sheet has been revised according to regulation EC No 1907/2006, and

regulation EU No 453/2010 (REACH) with classification according to Regulation (EC) No

1272/2008 as amended.

AOEL Acceptable operator exposure level

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level

DNEL Derived No Effect Level

EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic

PNEC Predicted No Effect Concentration

STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

ISSUE DATE: 2020-01-24

Version: 4



Ekoflock 50-100

Training requirements:

As with all hazardous chemicals, should all handling be done correctly and with care by trained personnel.

Disclaimer:

The information provided in this safety data sheet relates only to this specific product and may not be valid for the product if used with other materials in any process. The information is, at the time of publication, to the best of the Company's knowledge and belief, accurate and reliable. However, no warranty, guarantee or representation is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability for his own purpose. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question.

ISSUE DATE: 2020-01-24

Version: 4