

RFA 7/8" COAXIAL CABLE
NK CODES
RFA 7/8"-50
RFA 7/8"-50 BHF (UL) CATVR
RFA 7/8"-50 GHF Cca
RFA 7/8"-50 BHF Cca
NKRFA07800
NKRFA07804
NKRFA07811
NKRFA07812
CONSTRUCTION


Inner conductor	Copper tube	Ø 9.4 mm	(0.37 in)
Dielectric	Cellular polyethylene	Ø 22.5 mm	(0.89 in)
Outer conductor	Corrugated copper tube	Ø 25.4 mm	(1.00 in)
Jacket	See Jacketing Options table below	Ø 27.8 mm	(1.09 in)
Marking	Draka, cable type, manufacture week, year, batch number and meter mark		

ELECTRICAL CHARACTERISTICS at +20°C (+68°F)

Characteristic impedance	50 ± 1 Ω
Return loss 24 dB for 100 m cable with NKC connectors	
- 380 - 500	MHz
- 790 - 960	"
- 1710 - 1880	"
- 1900 - 2170	"
- 2490 - 2700	"
Other bands also available on request	
Bands according to customer's specifications	
Attenuation	See table
Velocity factor	0.90
Capacitance	74.2/m (22.8 pF/ft)
Maximum frequency	5100 MHz
Max power rating	See table
Peak RF voltage rating	3.3 kV
Peak power rating	95.0 kW
DC-resistance	
- Inner conductor	1.90 Ω/km (0.58 Ω/1000 ft)
- Outer conductor	1.39 Ω/km (0.42 Ω/1000 ft)

MECHANICAL CHARACTERISTICS

Weight (PE jacket)	0.43 kg/m	(0.29 lb/ft)
Weight (GHF/BHF fire retardant jacket)	0.48 kg/m	(0.32 lb/ft)
Maximum pulling force	2100 N	(472 lb)
Minimum bending radius		
- Single bending	120 mm	(4.7 in)
- Repeated bending	240 mm	(9.4 in)
Operating temperature range	-55...+85°C	(-67...+185 °F)
Crush resistance	1.6 kg/mm	(90 lb/in)
Bending moment	14.0 Nm	(10.3 lb-ft)
Recommended clamp spacing	1.0 m	(3.3 ft)

JACKETING OPTIONS

TYPE	JACKET	IEC 60754 -1/-2 halogen free, non corrosive	IEC 61034 low smoke emission	IEC 60332-3-24 fire retardant	CPR class	UV retardancy	UL Rated	Min. installation temperature
RFA 7/8"-50	Black, halogen free polyethylene (LDPE with HDPE skin)	yes	no	no	no	yes	no	-40°C (-40°F)
RFA 7/8"-50 GHF Cca	Grey, halogen free fire retardant thermoplastic	yes	yes	yes	C-s1d1a1	no	no	-20°C (-4°F)
RFA 7/8"-50 BHF Cca	Black, halogen free fire retardant thermoplastic	yes	yes	yes	C-s1d1a1	yes	no	-20°C (-4°F)
RFA 7/8"-50 BHF (UL) CATVR	Black, halogen free fire retardant UL Riser rated jacket	yes	yes	yes	no	yes	yes	-20°C (-4°F)

RFA 7/8" COAXIAL CABLE

FREQUENCY MHz	ATTENUATION dB/100 m	ATTENUATION dB/100 ft	POWER RATING kW
10	0.346	0.105	27
30	0.603	0.184	16
50	0.782	0.238	12
88	1.04	0.318	8.9
100	1.12	0.340	8.4
108	1.16	0.354	8.0
174	1.48	0.452	6.3
200	1.60	0.486	5.8
300	1.97	0.601	4.7
400	2.29	0.699	4.0
450	2.44	0.744	3.8
500	2.58	0.787	3.6
512	2.61	0.797	3.5
600	2.84	0.867	3.2
700	3.09	0.942	3.0
800	3.32	1.01	2.8
850	3.43	1.05	2.7
890	3.52	1.07	2.6
900	3.54	1.08	2.6
950	3.64	1.11	2.5
960	3.66	1.12	2.5
1000	3.74	1.14	2.5
1200	4.14	1.26	2.2
1400	4.50	1.37	2.0
1600	4.84	1.48	1.9
1800	5.17	1.58	1.8
1900	5.33	1.62	1.7
2000	5.48	1.67	1.7
2200	5.78	1.76	1.6
2400	6.07	1.85	1.5
2600	6.35	1.94	1.4
2800	6.63	2.02	1.4
3000	6.89	2.10	1.3
3400	7.40	2.26	1.2
3500	7.53	2.29	1.2
3600	7.65	2.33	1.2
4000	8.13	2.48	1.1
5000	9.26	2.82	0.97

Attenuation values are typical at ambient temperature +20°C (+68°F).

Power rating ambient temperature +40°C (+104°F), inner conductor +100°C (+212°F).

CODES FOR NKC CONNECTORS

CONNECTOR TYPE	CODE
N male	NKC1078300
N female	NKC1078400
7-16 male	NKC1078100
7-16 female	NKC1078200
7-16 male Right angle	NKC1078500
7-16 Bulkhead female	NKC1078290