



Neptune 002 with LED light source and sensor

Description

Neptune is a quality fitting in an oval shape (002) made of high pressure die-cast aluminium. Diffuser in UV- and vandal resistant polycarbonate. The front ring is fixed with 4 torx screws in stainless steel which are given a Delta seal treatment. IP65 class I

Application areas

P-house, facades, entrances, stairs, pedestrian areas, underpasses and tunnels.

Mounting

Direct in ceiling or on wall.

Installation

The fitting is prepared both for open and hidden installation. Push in terminal block 3x2x2,5 mm² with through-wiring possibilities.

Light source

- 1100 lm - 3000 K 12W
- 1100 lm - 4000 K 12W
- Life time 50.000 hours
- Light level equal to 26W compact lamp

Additional

The sensibility is adjusted on the microwave sensor. Likewise the hold time (exposure time after detected movement) might be adjusted (5 sek - 25 min).

The sensor has also a setting for a twilight function (2 - 30 lux).

Classic Detect can also be used as Master for other fittings.

Number	Type	Decor	Diffuser	Colour	Light source	Weight (kg)
111880	Neptune002	Cross	Opal	White	LED 840 1x12W	1,8
111881	Neptune002	Cross	Opal	Black	LED 840 1x12W	1,8
111878	Neptune002	Cross	Opal	White	LED 830 1x12W	1,8
111892	Neptune002 detect	Cross	Opal	White	LED 840 1x12W	1,9
111893	Neptune002 detect	Cross	Opal	Black	LED 840 1x12W	1,9
111890	Neptune002 detect	Cross	Opal	White	LED 830 1x12W	1,9
111891	Neptune002 detect	Cross	Opal	Black	LED 830 1x12W	1,9

Other versions of Neptune are available on request

NB!

A microwave sensor detect all forms of movement, not only from people and animals.

This means that the sensor might detect movements for instance from branches or leaves.

Please allow for this when installing the fitting to avoid unwanted functions.