

### Specification

Nominal Voltage	12V
Watts(15min Rate)	33.3 Watts at 1.67V/cell
Dimension	Length 151±2mm (5.95 inches)
	Width 65±1mm (2.56 inches)
	Container Height 93.5±1mm (3.68 inches)
	Total Height (with Terminal) 99±1mm (3.90 inches)
Approx Weight	Approx 2.66 kg (5.87lbs)
Terminal	T1 / T2
Container Material	ABS
Rated Capacity	8.60 AH/0.43A (20hr, 1.80V/cell, 25°C/77°F)
	7.98 AH/0.798A (10hr, 1.80V/cell, 25°C/77°F)
	7.10AH/1.42A (5hr, 1.75V/cell, 25°C/77°F)
	6.45 AH/2.15A (3hr, 1.75V/cell, 25°C/77°F)
	5.96 AH/5.96A (1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	135A (5s)
Internal Resistance	Approx 17mΩ
Operating Temp. Range	Discharge : -15~50°C (5~122°F)
	Charge : 0~40°C (32~104°F)
	Storage : -15~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)
Cycle Use	Initial Charging Current less than 2.7A. Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C
	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C
Capacity affected by Temperature	40°C (104°F) 103% 25°C (77°F) 100% 0°C (32°F) 86%
Self Discharge	CT series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.



### Applications

- ◆ UPS (High rate)
- ◆ High power backup supply
- ◆ Emergency power supply
- ◆ Starting system
- ◆ Power tools
- ◆ Emergency lighting
- ◆ Electric starting

### Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	28.6	19.1	15.0	12.4	9.24	6.71	5.24	2.84	2.03	1.61	1.34	1.16	0.927	0.776	0.421
1.80V/cell	32.1	20.9	16.2	13.2	9.65	6.95	5.43	2.93	2.09	1.64	1.38	1.19	0.956	0.798	0.430
1.75V/cell	35.3	22.1	17.2	13.9	10.0	7.20	5.61	3.03	2.15	1.70	1.42	1.23	0.994	0.819	0.439
1.70V/cell	37.6	23.3	18.0	14.3	10.4	7.42	5.75	3.12	2.22	1.75	1.46	1.26	1.00	0.834	0.444
1.67V/cell	39.3	24.1	18.5	14.8	10.7	7.60	5.86	3.17	2.26	1.79	1.49	1.28	1.02	0.843	0.447
1.60V/cell	40.5	25.0	18.9	15.1	10.9	7.72	5.96	3.22	2.28	1.81	1.51	1.30	1.03	0.850	0.450

### Constant Power Discharge (Watts/cell) at 25 °C (77°F)


F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	52.8	35.6	28.2	23.5	17.6	12.9	10.1	5.50	3.95	3.14	2.63	2.28	1.83	1.54	0.836
1.80V/cell	58.4	38.4	30.1	24.7	18.2	13.2	10.4	5.66	4.06	3.20	2.69	2.34	1.88	1.58	0.851
1.75V/cell	63.4	40.1	31.6	25.7	18.8	13.6	10.7	5.82	4.15	3.30	2.78	2.41	1.95	1.61	0.867
1.70V/cell	66.5	41.8	32.6	26.3	19.4	14.0	10.9	5.97	4.27	3.39	2.84	2.46	1.97	1.64	0.877
1.67V/cell	68.4	42.6	33.3	27.0	19.8	14.2	11.1	6.05	4.33	3.45	2.89	2.49	2.00	1.65	0.881
1.60V/cell	69.5	43.6	33.6	27.2	20.0	14.3	11.2	6.12	4.37	3.47	2.92	2.52	2.01	1.67	0.885




## Dimensions

### T1 Terminal


Unit: mm [inches]




## Discharge Characteristics





## Float Charging Characteristics



## Temperature Effects in Relation to Battery Capacity



## Effect of Temperature on Long Term Float Life



## Self Discharge Characteristics

- A** No supplementary charge required  
(Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
  1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
  2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
  3. Charged for 8-10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity.  
The battery should never be left standing till this is reached.

## Sales Office

### Sweden

Cell tech AB,  
Äggelundavägen 2, 175 12 Järfälla, Sweden  
TEL: +41 8 445 7870  
FAX: +41 8 445 7878  
E-mail: order@celltech.se  
www.celltech.se

### Finland and Baltic countries

Celltech oy  
Höyläämötie 11A, 00380 Helsinki, Finland  
TEL: +358 (0)207 999 1 40  
FAX: +358 (0)207 999 1 41  
E-mail: info@celltech.fi  
www.celltech.fi

### Denmark

Celliech A/S  
Lejrvej 25, 3500 Værløse Denmark  
TEL: +45 7025 2201  
FAX: +45 7025 2202  
E-mail: info@celliech.dk  
www.celliech.dk