

Feilo Sylvania International Group Kft.Duna Tower – Building B, 3rd Floor
22 Népfürdő Street
Budapest
H-1138
HungaryT +36 1 88 05 900
www.sylvania-group.com

A Feilo Sylvania Company

October 08th, 2025**MANUFACTURERS DECLARATION:**

Related to International Featured Standards (IFS Food), British Retail Consortium (BRC) and HACCP-Concept

Feilo Sylvania confirms that products from the LED luminaire group 'RESISTO GRP', with code numbers as listed on the next page, are developed, manufactured and tested in accordance with applicable legal rules and in conformity with the standards below :

EN 60598-1 (2021) + A11 :2022 Luminaires – Part 1: General requirements and tests**EN 60598-2-1 (2021) Luminaires - Part 2-1: Particular requirements - Fixed general purpose luminaires**

Product Codes : See next page

Appropriate measures were taken on these products to minimize the risk of breakage and make them suitable for use in food applications in accordance with the International Featured Standard IFS Food.

'RESISTO GRP' LED luminaires meet the IFS requirements by offering impact resistant cover according to EN 60598-1 section 4.13 and good cleanability. The cleaning of the luminaires must solely be done with PH neutral cleaners. Advice on chemical compatibility (cleaning chemicals & procedures) with our luminaires and accessories should be obtained by contacting our local sales organization.

When proper installation and appropriate handling is ensured in line with the IFS requirements, there is no risk of luminaire breakage and contamination of food caused by parts of fixed lighting equipment.

For any further questions you may have, please feel free to contact us at any time.

Kind regards,
Hugo Smolders**Compliance Manager**

Feilo Sylvania Lighting Belgium NV

Ondernemerslaan 5429

B-3800 Sint-Truiden, Belgium

T +32 477 48 44 79

E hugo.smolders@sylvania-lighting.com

Product Codes : RESISTO GRP LED IP66

Item Code	Product Description
0010519	Resisto GRP 1200 IP66 4200-7000lm 840
0010520	Resisto GRP 1500 IP66 5100-8500lm 840