

TECHNICAL FOLDER
FILTERCEL HT6
Specifications

Code	H620254
Name	HT6
Description	PLEATED FILTER CELL

Applications

Spray booths and paint drying oven filtration. Pre-filtration and filtration with temperature up to 300°C.

Sizes

dimensions	500x625x98	mm
------------	------------	----

Technical data

filter medium composition	glass microfiber
frame material	galvanized sheet
regeneration	no
max. working temperature	300 °C
max. working R.H.	90 %

Funcional data

nominal air flow	1600	m ³ /h
initial pressure drop	60	Pa
final pressure drop	300	Pa
colorimetric efficiency	65	%
classification (EN 779:2012)	M6	
classification (ISO 16890)	ePM2,5 50	%
flame resistance	2 (U.L.)	

Rev. 00_19

GENERAL FILTER HEADQUARTER

Via Emilia, 23
 31038 Paese (TV), Italia
 Tel: +39 0422 4594
 Fax: +39 0422 459590
 www.generalfilter.com
 info@generalfilter.com

GENERAL FILTER ITALIA

Via Morgagni, 40 int. 7/8
 20010 Pogliano Milanese (MI), Italia
 Tel: +39 02 93550640
 Fax: +39 02 93255670
 Italia: sales.ita@generalfilter.com
 Estero: sales.int@generalfilter.com

GENERAL FILTER FRANCE

13 Avenue d'Aygu
 26200 Montlimar, France
 Tel: +33 987876598
 Fax: +33 987876599
 r.meucci@generalfilter.fr

GENERAL FILTER IBERICA

C/Cabo Ortegá, nrs. 3-5 LA POVEDA
 28500 Arganda del Rey, Madrid,
 España
 Tel: +34 91 8719046
 Fax: +34 91 8719054
 gefisa@generalfilter.com

GENERAL FILTER HAVAK

Sanayi Sitesi P. Blok No. 10
 Hosdere Mevkii
 34517 Esenyurt, Istanbul, Türkiye
 Tel: +90 212 623 0074
 Fax: +90 212 623 0075
 info@generalfilterhavak.com