

CHARGING AND RECOVERY CYLINDERS



1. REFRIGERANT RECOVERY CYLINDERS

- These different sized ITE recovery cylinders have a double valve (blue/red) with 1/4" male flare SAE connections.
- Test pressure 42 bar.
- Can be used for R410A.
- Manufactured according to EC 1322-1.

RCYL-12L RECOVERY CYLINDER

- Cylinder volume: 12,5 L
- Height: 50 cm
- Diameter: 23,3 cm
- Tare weight: 7,50 kg

RCYL-30L RECOVERY CYLINDER

- Cylinder volume: 27,2 L
- Height: 64 cm
- Diameter: 30 cm
- Tare weight: 14 kg

RCYL-50L RECOVERY CYLINDER

- Cylinder volume: 61 L
- Height: 115 cm
- Diameter: 30 cm
- Tare weight: 28 kg
- Other cylinders available upon request.

2. HEATING BELTS

RCH-10 HEATING BELT with springs RCH-10/V2 HEATING BELT with elastics

- For max temperature of +60°C (+140°F)
- Power consumption: 230 V / 400 W
- Dimensions

Length:	70 cm
Width:	8 cm
Minimum Ø:	23 cm
Maximum Ø:	32,5 cm
- See page 193

