

## “ ITE “ ELECTRONIC CHARGING & RECOVERY UNITS

### WS-005

### DIGITAL WEIGHING SCALE

#### FEATURES

- Maximum weight capacity: **5000 g**.
- Accuracy: **0,5 g**.
- Operating temperature: **15°C to 30°C**.
- 3 batteries AA (1,5 V) included.
- Low battery indication.
- Auto power off (after 15 minutes without any change in weight, the scale will turn off. This auto off time of 15 min can be extended).
- Three display modes g, lb, oz.
- Can also be operated on 220 V.
- **Supplied with CE mark.**

### WS-005-1L-1/4

### DIGITAL WEIGHING SCALE

equipped with refrigerant bottle valve with 1/4" connection (+ depressor pin).

### WS-005-1L-5/16

### DIGITAL WEIGHING SCALE

equipped with refrigerant bottle valve with 5/16" connection (+ depressor pin).

### WS-005-1L-7/16

### DIGITAL WEIGHING SCALE

equipped with refrigerant bottle valve with 7/16" connection (+ depressor pin).

#### ACCESSORIES AND SPARE PARTS

### BVS-1L

Refrigerant bottle valve 7/16" x 1/4" MFL

### BVS-1L-WS-005-1/4 SAE

Refrigerant bottle valve for WS-005 1/4" FFL (+ depressor pin) x 1/4" MFL acces valve (+core)

### BVS-1L-WS-005-5/16 SAE

Refrigerant bottle valve for WS-005 5/16" FFL (+ depressor pin) x 1/4" MFL acces valve (+core)

### BVS-1L-WS-005-7/16 SAE

Refrigerant bottle valve for WS-005 7/16" FFL (+ depressor pin) x 1/4" MFL acces valve (+core)

### WS-055

### WEIGHING AND RECOVERY SCALE

#### FEATURES

- Designed for both charging and recovery. Can be used with **all** refrigerants and hydrocarbons.
- **55 kg** (120 lb) max capacity.
- Resolution selectable: **5 g** / 0,2 oz / 0,010 lb  
**2 g** / 0,1 oz / 0,005 lb
- Accuracy: **± 0,01 %** of reading at 55 kg.
- Control function (with or without optional valve module): the scale can be programmed to a desired weight, so that when this value is reached, the scale will sound a signal.
- **9 V** battery (included) powers all functions.
- Battery life approximately **60 hours** (30 hours when using optional valve).
- Three display modes: kg, lb or lb-oz.
- Rugged removable platform with independent removable control module (including retractable table stand/hanging hook option).
- Auto power off (after 15 minutes without any change in weight the scale will turn off. This auto off time of 15 min can be extended.).
- Possible to zero scale at any point.
- Low battery indication.
- Operating temperature: **0°C to +40°C** (32°F to +104°F).
- Level sight glass and adjustable feet for perfect level measurement
- Weight: **4,25 kg** (9,4 lb) including carrying case  
**3,05 kg** (6,7 lb) scale only.
- Carrying case dimensions: **430 mm x 330 mm x 100 mm** (17" x 13" x 4").
- Platform dimensions: **280 mm x 280 mm** (11" x 11").
- Supplied in tough ABS case.
- **Supplied with CE mark.**

