



Singlemode patch cords are used for telecom networks and also used for high speed metropolitan and access network. The Singlemode patch cords are manufactured using LSZH cables which conform to IEC, EIA TIA or Telcordia standards. The OS2 patch cords are terminated with standard connectors which give optimum optical performance.

Features

- SC, LC, ST, FC MU and E2000 connectors
- UPC and APC connectors
- Low smoke zero halogen (LSZH) jacket in yellow colour
- 900µm tight buffer
- OS1/OS2 fibre conforms to ITU-652.D, TIA/EIA 492 CAAA
- Simplex and duplex assemblies
- Duplex assemblies available with clips (SC and LC)
- Different connector performance range for specific application
- Armoured option also available

Applications

- CATV / Video
- Passive Optical Network PON
- WDM / DWDM
- FTTH
- Data centers
- Supports high speed multi channel video, data and voice services in metropolitan and access networks

ATM, SONET and WDM

Specification

Connector Specification

OPTICAL PERFORMANCE SINGLEMODE CONFORMANCE

IL Max/Master (Acceptance) 0.25dB IEC 61300-3-4 Ave/Master 0.18dB IEC 61300-3-4 Ave/Random 0.18dB IEC 61300-3-34 Return Loss 55/65dB IEC 61300-3-6

Cable Specification

CHARACTERISTICS	SIMPLEX	DUPLEX
Cable Material	LSZH	LSZH
Strength Member	Aramid	Aramid
Crush (N)	1000	1000
Operating Temperature (°C)	-20 to 60	-20 to 60
Fire Specification	IEC 60332-1	IEC 60332-1

Fibre Specification

CHARACTERISTICS

0.38 @ 1310nm / 0.25 @ Attenuation (dB) / km

1550nm

Chromatic Dispersion (ps/nm x km) 3.0 @ 1310nm / 18.0 @ 1550nm

Ordering Information

Connec	tor End A	Connector End B		
FC	FC FC		FC	
FCA	FCA	FCA	FCA	
SC	SC	SC	SC	
SCA	SCA SCA		SCA	
ST	ST	ST	ST	
LC	LC	LC	LC	
LCA	LCA	LCA	LCA	
MU	MU	MU	MU	
MTRJ MTRJ* E2 E2000		MTRJ	MTRJ*	
		E2	E2000	

ST	ST	ST	ST	
LC	LC	LC	LC	
LCA	LCA	LCA	LCA	
MU	MU	MU	MU	
MTRJ	MTRJ*	MTRJ	MTRJ*	

* MTR	l is	only	available i	in N	4iniZip	duple	2

Mode			Cable Configuration			
09 OS1/OS2		S	Simplex			
		D	Duplex			
		FD	Flat Duplex			

	Cable Colour			
	YE	Yellow		
ľ				

Cable Length				
1	1 metre			
2	2 meter			
3	3 meter			
5	5 meter			
10	10 meter			
хх	Specify			

	Example Part Number							
	FC SC 09 S YE 3							
This wast asserted as 2 marked a 2 marked aircraft of the CC OCI/OC2 market are also walled								

This part number has created a 3 metre simplex FC to SC OS1/OS2 patch cord in yellow.



Further Information

- For additional information please contact your sales representative
- Downloaded from http://www.fibrefab.com/products/patch-cords/os2-sm-simplexduplex-patch-cord/
- FibreFab reserves the right to make changes to the product specifications in this datasheet at any time without notice
- Information in this document is correct as of June 11, 2014

Europe

- +44 870 127 3330 sales@fibrefab.com
- © FibreFab 2014

Americas

Middle East & Africa

Asia Pacific

- asia@fibrefab.com