



Our range of high quality SC adaptors have high precision alignment sleeves for reliability and improved reconnectability. For singlemode applications a ceramic sleeve is supplied to ensure a high precision alignment. For multimode applications a phosphor bronze sleeve is supplied. The housing is available in different colours with options for flange or flangeless body, metal clips or inbuilt clips.

Features

- Complies with IEC 61754-4 and IEC 60784-14 standards
- High precision alignment sleeve
- Low insertion loss and improved reconnectability
- RoHS, REACH SvHC compliant
- Available in simplex and duplex adaptors
- Also available are SC simplex adaptors with a shutter

Applications

- Data centres
- Premise installations
- Telecommunication networks
- Ethernet, Fibre channel, ATM, LAN, MAN and WAN

Specification

	Ceramic	Phosphor Bronze	Conformance
Insertion Loss (Typ)	0.1dB	0.15dB	IEC 61300-3-4
Mating Durability	-	500	IEC 61300-2-2
Receptacle Retention Force	-	2N - 5.9N	IEC 61754-4
Operating Temperature	-	-25 to +70, 12 cycles	IEC 61300-2-22

Ordering Information

MODE	TYPE	COLOUR	PART NO.	
			SIMPLEX	DUPLEX
SM	APC	GREEN	SCAPCUSGREEN	SCAPCUDGREEN
SM	PC	BLUE	SCUSZR02	SCUDZR02
MM	PC	BEIGE	SCUSPHBRBEIGE	SCUDPHBRBEIGE
MM	PC	AQUA	SCSMPXAQUA	SCDPXAQUA



Further Information

- For additional information please contact your sales representative
- Downloaded from <http://www.fibrefab.com/products/adaptors/sc-adaptors/>
- FibreFab reserves the right to make changes to the product specifications in this datasheet at any time without notice
- Information in this document is correct as of May 28, 2014

Europe

- +44 870 127 3330
- sales@fibrefab.com

Americas

- +1 410 242 9026
- sales@fiberfabinc.com

Middle East & Africa

- +971 4 443 0168
- mea@optronicsnet.com

Asia Pacific

- +86 755 2561 3694
- asia@fibrefab.com