



Singlemode pigtails are used in telecom, datacom networks and also used for high speed metropolitan and access network. The singlemode pigtail buffer conforms to IEC, EIA TIA or Telcordia standards. The singlemode pigtails are terminated with standard connectors which gives optimum optical performance.

Features

- SC, LC, ST, FC and E2000 Connectors
- UPC and APC Connectors
- Low smoke zero halogen (LSZH) buffer
- 900µm tight buffer or easy strip structure
- OS1/OS2 optical fibre conforms to ITU-G652.D, TIA/EIA 492 CAAA
- OS1/OS2 bend insensitive optical fibre conforms to ITU-G657.A1 or A2
- Different connector performance range for specific application
- Available in standard white colour buffer and also in standard 12 colours as per IEC 60304
- Available in standard and blister packing

Applications

- Telecom and datacom application
- Patch panels, wall boxes, ODFs and splice cassettes
- Easy strip Pigtails for on site installation
- Supports high speed multi channel video, data and voice services in metropolitan and access networks
- ATM, SONET and WDM

Specification

Connector Specification

OPTICAL PERFORMANCE SINGLEMODE CONFORMANCE

 IL Max/Master (Acceptance)
 0.25dB
 IEC 61300-3-4

 Ave/Master
 0.18dB
 IEC 61300-3-4

 Ave/Random
 0.18dB
 IEC 61300-3-34

 Return Loss
 55/65dB
 IEC 61300-3-6

Cable Specification

CHARACTERISTICS SIMPLEX DUPLEX

Crush N/100mm 500 Operating Temperature $^{\circ}$ C -21 to 60 Nominal buffer Diameter μ m 900 + 50

Max Tensile Load N 6

Ordering Information

Connector End				
SC	SC			
SCA	SC APC			
LC	LC			
LCA	LC APC			
FC	FC			
FCA	FC APC			
ST	ST			
E2	E2000			
E2A	E2000 APC			

Fibre Type				
09	OS1/OS2			
7A1	G.657A1			
7A2	G.657A2			

В

Cable Length		Cable Construction	
1	1 metre		Tight Buffer
2	2 metre	-12/1B	Tight Buffer - Pack of 12 colours
3	3 metre	-12/1BP	Tight Buffer - Blister pack of 12
5	5 metre	EASY	Easy strip
10	10 metre	E-12/1B	Easy strip - Pack of 12 colours
ХХ	Specify	E-12/1BP	Easy strip - Blister pack of 12

Example Part Number

SC	09	В	5	-12/1B

This part number has created a 5 metre SC OS1/OS2 pack of 12 pigtails in different colours.



Further Information

- For additional information please contact your sales representative
- Downloaded from http://www.fibrefab.com/products/pigtails/os1-os2-singlemode-pigtail/
- FibreFab reserves the right to make changes to the product specifications in this datasheet at any time without notice
- Information in this document is correct as of June 11, 2014

Europe

- **+** +44 870 127 3330
- sales@fibrefab.com

© FibreFab 2014

Americas

- **+** 1 410 242 9026
- sales@fiberfabinc.com

Middle East & Africa

- **+ + 971 4 443 0168**
- mea@optronicsnet.com

Asia Pacific

- +86 755 2561 3694
- asia@fibrefab.com