



SAP	dimensions				type	loading ratings (kN)		thermal speed ratings [rpm]	limited speed ratings [rpm]	weight kg
	d	D	B	r1,r2 min		dyn. Cr	stat. C0r	n ₀	n _{0.1}	
*	75	115	20	1,1	6015	39,5	33,5	6400	*	0,643
*	75	115	20	1,1	6015-RS	39,5	33,5	–	3700	0,643
*	75	115	20	1,1	6015-2RS	39,5	33,5	–	*	0,643
*	75	115	20	1,1	6015-Z	39,5	33,5	–	*	0,643
*	75	115	20	1,1	6015-ZZ	39,5	33,5	–	*	0,643
*	75	130	25	1,5	6215	66	49,5	5900	*	1,21
*	75	130	25	1,5	6215-RS	66	49,5	–	6700	1,21
ANQ819	75	130	25	1,5	6215-2RS	66	49,5	–	*	1,21
ANQ820	75	130	25	1,5	6215-2RS-C3	66	49,5	–	3200	
*	75	130	25	1,5	6215-Z	66	49,5	–	*	1,21
ANQ821	75	130	25	1,5	6215-ZZ	66	49,5	–	*	1,21
ANQ822	75	130	25	1,5	6215-ZZ-C3	66	49,5	–	4800	
*	75	160	37	2,1	6315	114	77	6300	*	3,12
*	75	160	37	2,1	6315-RS	114	77	–	2700	3,12
*	75	160	37	2,1	6315-2RS	114	77	–	*	3,12
*	75	160	37	2,1	6315-Z	114	77	–	*	3,12
*	75	160	37	2,1	6315-ZZ	114	77	–	*	3,12
*	75	190	45	3	6415	154	114	5600	*	6,75
*	80	100	10	0,6	61816	15,9	16,8	4600	*	0,15
*	80	110	16	1	61916	27,6	25,3	5600	*	0,4
*	80	125	14	0,6	16016	33,1	31,4	4700	*	0,615
*	80	125	22	1,1	6016	51	42	6100	*	0,85
*	80	125	22	1,1	6016-RS	51	42	–	3300	0,85
*	80	125	22	1,1	6016-2RS	51	42	–	*	0,85
*	80	125	22	1,1	6016-Z	51	42	–	*	0,85
*	80	125	22	1,1	6016-ZZ	51	42	–	*	0,85
*	80	140	26	2	6216	72	54	5500	*	1,42
*	80	140	26	2	6216-RS	72	54	–	6000	1,42
ANQ823	80	140	26	2	6216-2RS	72	54	–	*	1,42
ANQ824	80	140	26	1,5	6216-2RS-C3	72	54	–	3000	
*	80	140	26	2	6216-Z	72	54	–	*	1,42
ANQ825	80	140	26	2	6216-ZZ	72	54	–	*	1,42
ANQ826	80	140	26	1,5	6216-ZZ-C3	72	54	–	4500	
*	80	170	39	2,1	6316	123	87	5500	*	3,73
*	80	170	39	2,1	6316-RS	123	87	–	*	3,73
*	80	170	39	2,1	6316-2RS	123	87	–	2500	3,73

ONNLINE LAAKERIT / BEARINGS
* PLEASE ASK MORE INFORMATION