



SAP	type	dimensions											loads (N)			weight			
		Ød1	N1	L2	H2	N2	ØN	L3	A1	H1	H	L	A2	L1	dyn.C	stat.C	bearing+sleeve	housing	kg
ANR086	UKT205	20	16	10	51	32	19	51	12	76	89	97	24	62	13300	7457	UK205+H2305	T205	0,86
ANR087	UKT206	25	16	10	56	37	22	57	12	89	102	113	28	70	18525	10735	UK206+H2306	T206	1,26
ANR088	UKT207	30	16	13	64	37	22	64	12	89	102	129	30	78	24415	14630	UK207+H2307	T207	2,5
ANR089	UKT208	35	19	16	83	49	29	83	16	102	114	144	35	89	27645	16910	UK208+H2308	T208	2,5
ANR090	UKT209	40	19	16	83	49	29	83	16	102	117	144	35	87	32395	20235	UK209+H2309	T209	2,51
ANR091	UKT210	45	19	16	83	49	29	86	16	102	117	149	35	90	33345	22135	UK210+H2310	T210	2,6
ANR092	UKT211	50	25	19	102	64	35	95	22	130	146	171	41	106	41230	27930	UK211+H2311	T211	4,26
ANR093	UKT212	55	32	19	102	64	35	102	22	130	146	194	46	119	49780	34390	UK212+H2312	T212	5,02
ANR094	UKT213	60	32	21	111	70	41	121	26	151	167	224	51	137	54340	38095	UK213+H2313	T213	6,56
ANR095	UKT215	65	32	21	111	70	41	121	26	151	167	232	48	140	64030	45885	UK215+H2315	T215	7,52
ANR096	UKT216	70	32	21	111	70	41	121	26	165	184	235	51	140	69065	50350	UK216+H2316	T216	8,56
*	UKT217	75	38	29	124	73	48	157	30	173	198	260	54	162	79800	58805	UK217+H2317	T217	11,38

* = huomio: kartioholkki myydään aina erikseen

* = note: adapter sleeve is always sold separately