



SAP	type	ø d	L	Dimensions							bolt size load ratings (N)					
				J	A2	A1	A	4-øN	A0	S	mm	dyn.	stat.	bearing housing	weight	
ANQ917	UCF201	12	86	64	15	12	25,5	12	31	12,7	M10	12160	6318	UC201	F204	0,6
ANQ918	UCF202	15	86	64	15	12	25,5	12	31	12,7	M10	12160	6318	UC202	F204	0,59
ANQ919	UCF203	17	86	64	15	12	25,5	12	31	12,7	M10	12160	6318	UC203	F204	0,58
ANQ920	UCF204	20	86	64	15	12	25,5	12	31	12,7	M10	12160	6318	UC204	F204	0,56
ANQ921	UCF205	25	95	70	16	14	27	12	34,1	14,3	M10	13300	7457	UC205	F205	0,8
ANQ922	UCF206	30	108	83	18	14	31	12	38,1	15,9	M10	18525	10735	UC206	F206	1,12
ANQ923	UCF207	35	117	92	19	16	34	14	42,9	17,5	M12	24415	14630	UC207	F207	1,46
ANQ924	UCF208	40	130	102	21	16	36	16	49,2	19	M14	27645	16910	UC208	F208	1,84
ANQ925	UCF209	45	137	105	22	18	38	16	49,2	19	M14	32395	20235	UC209	F209	2,15
ANQ926	UCF210	50	143	111	22	18	40	16	51,6	19	M14	33345	22135	UC210	F210	2,42
ANQ927	UCF211	55	162	130	25	20	43	19	55,6	22,2	M16	41230	27930	UC211	F211	3,31
ANQ928	UCF212	60	175	143	29	20	48	19	65,1	25,4	M16	49780	34390	UC212	F212	4,28
ANQ929	UCF213	65	187	149	30	22	50	19	65,1	25,4	M16	54340	38095	UC213	F213	4,99
ANQ930	UCF214	70	193	152	31	22	54	19	74,6	30,2	M16	59090	41895	UC214	F214	5,85
ANQ931	UCF215	75	200	159	34	22	56	19	77,8	33,3	M16	64030	45885	UC215	F215	6,91
ANQ932	UCF216	80	208	165	34	22	58	23	82,6	33,3	M20	69065	50350	UC216	F216	7,5
ANQ933	UCF217	85	220	175	36	24	63	23	85,7	34,1	M20	79800	58805	UC217	F217	9,66
ANQ934	UCF218	90	235	187	40	24	68	23	96	39,7	M20	91295	67925	UC218	F218	12,06