



SAP	type	d1	dimensions							bolt size	load ratings(N)		bearing+sleeve	housing	weight kg
			L	J	A2	A1	A	4-φN	A0		dyn. C	stat. G			
ANR038	UKF205	20	95	70	16	14	27	12	35,5	M10	13300	7457	UK205+H2305	F205	0,85
ANR039	UKF206	25	108	83	18	14	31	12	39	M10	18525	10735	UK206+H2306	F206	1,16
ANR040	UKF207	30	117	92	19	16	34	14	42,5	M12	24415	14630	UK207+H2307	F207	1,55
ANR041	UKF208	35	130	102	21	16	36	16	46,5	M14	27645	16910	UK208+H2308	F208	1,94
ANR042	UKF209	40	137	105	22	18	38	16	48,5	M14	32395	20235	UK209+H2309	F209	2,3
ANR043	UKF210	45	143	111	22	18	40	16	50	M14	33345	22135	UK210+H2310	F210	2,59
ANR044	UKF211	50	162	130	25	20	43	19	54,5	M16	41230	27930	UK211+H2311	F211	3,46
ANR045	UKF212	55	175	143	29	20	48	19	61	M16	49780	34390	UK212+H2312	F212	4,33
ANR046	UKF213	60	187	149	30	22	50	19	64	M16	54340	38095	UK213+H2313	F213	4,9
ANR047	UKF215	65	200	159	34	22	56	19	71	M16	64030	45885	UK215+H2315	F215	7,02
ANR048	UKF216	70	208	165	34	22	58	23	73,5	M20	69065	50350	UK216+H2316	F216	7,76
ANR049	UKF217	75	220	175	36	24	63	23	77	M20	79800	58805	UK217+H2317	F217	10,08
ANR050	UKF218	80	235	187	40	24	68	23	81,5	M20	91295	67925	UK218+H2318	F218	12,44

\* = huomio: kartioholkki myydään aina erkiseen

\* = note: adapter sleeve is always sold separately