

Product information



1. **Product name:**
2. **Type of product:** Writing and marking instrument with solid gel lead and actuation mechanic
3. **Contents:**
Solid gel lead (for details see separate safety sheet)
Shaft and cap: PP
Actuation mechanic: PP/POM
Color clip: POM
4. **General product properties / application tips**
 - 4.1 **Application areas:** Construction, industry, industrialised building, wood- and metal-work, welding store, shipping, consignment, forwarding, home & garden
 - 4.2 **Usable on:** All surfaces, especially suitable for critical surfaces as:
Dusty, raw, oily, damp, soiled, dark and elastic surfaces
Suitable for overwriting existing "normal" markings
Applicable under water
 - 4.3 **Removability:** With solvent from glossy surfaces
 - 4.4 **General properties:** Marking on all solid materials
Smooth dispensing of 8mm gel lead
Fast drying, highly permanent after drying (some minutes)
Excellent contrast even on dark surfaces by covering color application
Resistant against light and temperature
 - 4.5 **Application tips:** Application temperature: -20 ° to +70 °C

Markings good visible up to 800 ° C
Non-sensitive, cannot stick or block
Adjusting through twisting rotation part
While sharpening do not handle rotation part
5. **Quality features / convenience:**
 - ☐ Weatherproof markings
 - ☐ Also for dusty and critical surfaces
 - ☐ Strong, good visible markings
 - ☐ Can be kept open several days
 - ☐ Insensitive against drying out
 - ☐ Variable line width (~2-8mm)
 - ☐ Good and full color application
 - ☐ Replaces paint markers - no annoying "pumping" or sticking
 - ☐ No dripping paint, no blobs
 - ☐ Ideal for outdoor use
 - ☐ Sharpener inside the front of the cap
 - ☐ Easy handling cuiver cap
6. **Storage:** With tight closed cap storable up to 3 years at 10 ° - 20 °C

