



Portable Fan Heater 3kW **CEE** plug



The fan heaters are designed for temporary or permanent heating for the possible use in constructions sites, in warehouses, workshops, weekend cottages and similar dry or wet areas. The ventilator motor has a low noise level and the specially shaped front grill controls the air flow and provides a wide heating area.



Product arguments

- Robust design in corrosion-resistant galvanized sheet steel, can easily be installed on the wall using the supplied bracket
- · Powerful fan motor with low noise level
- The heaters are designed for optimal air flow and guick heating
- The controlling screen on the front holds together the air flow, creating a greater throw length
- Intended for both temporary and permanent heating, IP 44 for use in damp areas
- \bullet Variable thermostat $5\,^\circ$ to $35\,^\circ$, controls the heat and fan alternatively only heat. Selected with the toggle switch on the control panel
- Supplied with 2 m cable with CEE connection plug 16A/400 V
- The overheating protection is reset manually on the control panel, the fan is equipped with a post-cooling thermostat
- Do not load N (neutral)
- Timer with up to 14 h switching delay, can be reconnected as a running time timer

Article No.: E8726313

Type: VF 3T



Certifications:













Technical Data, VF 3T

Incoming 5-pol/400V 16A CEE 416-6 1 pcs

Incoming Cable Length / Area Cable / Connector 2m/4G1.5/416P6 CEE

Rated current 4,3 A

Voltage 3~400 V

Output modes 0 - 1,5 - 3 kW

Timer 14 h

Air flow 400 m3/h

Noise level 38 dB(A)

Weight 8 kg

Dimensions H x W x D (mm) 370x310x360 mm

Protection class IP44