



Portable Fan Heater 3kW **CEE** inlet



The fan heaters are designed for temporary or permanent heating for the possible use in constructions sites, in warehouses, workshops, weekend cottages and similar dry or wet areas. The ventilator motor has a low noise level and the specially shaped front grill controls the air flow and provides a wide heating area.



Product arguments

- Robust design in corrosion-resistant galvanized sheet
- Powerful fan motor with low noise level
- The heaters are designed for optimal air flow and quick heating
- The controlling screen on the front holds together the air flow, creating a greater throw length
- Intended for both temporary and permanent heating, IP 44 for use in damp areas
- Variable thermostat 5° to 35°
- 16a CEE plug direct on the fan
- The overheating protection is reset manually on the control panel
- Timer with up to 14 h switching delay, can be reconnected as a running time timer
- Do not load N (neutral)

Article No.: E8726315

Type: VF 3BT



Certifications:













Technical Data, VF 3BT

Incoming 5-pol/400V 16A CEE 416-6 1 pcs

Rated current 4,3 A

Voltage 3~400 V

Output modes 0 - 1,5 - 3 kW

Timer 14 h

Air flow 400 m³/h

Noise level 38 dB(A)

Weight 8 kg

Dimensions H x W x D (mm) 370x310x360 mm

Protection class IP44