SAFETY DATA SHEET

Labko® BioVision flocculation chemical

SDS according to Regulation (EC) No. 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), Annex II-EU

SECTION 1: Identification of the substance / mixture and of the company / undertaking

 Date issued
 26.11.2021

 Revision date
 07.12.2021

1.1. Product identifier

Product name Labko® BioVision flocculation chemical
UFI 3GQG-02JP-TC0D-WM30

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance / preparation Water treatment chemical Flocculant.

Uses advised against Do not use for non-identified uses.

1.3. Details of the supplier of the safety data sheet

Company name Wavin Finland Oy Office address Visiokatu 1 Postcode 33720 City Tampere Country Finland Email myynti@wavin.com Website www wavin.com Enterprise No. 0154311-1

1.4. Emergency telephone number

Emergency telephone Description: Poison Information Centre, Tukholmankatu 17, P.O.Box 790, FI-00029 HUS Helsinki), Finland tel. (24 h) / 09-4711 (exchange), 09-471977 (direct)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP / GHS]

Eye Dam. 1; H318

Met. Corr. 1; H290

2.2. Label elements

Hazard pictograms (CLP)



Signal word Danger

Hazard statements H318 Causes serious eye damage.

H290 May be corrosive to metals.

Precautionary statements P102 Keep out of reach of children.

P264 Wash kädet thoroughly after handling.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray. P280 Wear protective gloves/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P301 IF SWALLOWED: P310 Immediately call a POISON CENTER or doctor /

physician.

P101 If medical advice is needed, have product container or label at hand.

2.3. Other hazards

PBT / vPvB This product does not contain any PBT or vPvB substances.

Other hazards The product may affect the acidity (pH-factor) in water with risk of harmful effects to aquatic organisms. When heated, toxic and corrosive vapours/gases may be formed.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Substance	Identification	Classification	Contents	Notes
Polyaluminium chloride	CAS No.: 1327-41-9	Met. Corr. 1; H290	24 - 35 %	
	EC No.: 215-477-2	Eye Dam. 1; H318		
	REACH Reg. No.:			
	01-2119531563-43			

SECTION 4: First aid measures

4.1. Description of first aid measures

General	IF exposed or concerned: Get medical advice/attention. If medical advice is needed, have product container or label at hand.
Inhalation	Move into fresh air and keep at rest. IF exposed: Call a POISON CENTER or doctor/physician.
Skin contact	Rinse immediately contaminated clothing and skin with plenty of water before

	removing clothes. IF exposed: Call a POISON CENTER or doctor/physician.
Eye contact	Continue to rinse for at least 15 minutes and seek medical attention.
Ingestion	Immediately rinse mouth and drink plenty of water 200 - 300 ml). Do not induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

General symptoms and effects Corrosive. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Medical treatment Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials. The product
	is non-combustible.

5.2. Special hazards arising from the substance or mixture

Fire and explosion hazards	The product is non-combustible. If heated, toxic vapours may be formed.
Hazardous combustion products	Hydrogen chloride (HCI).

5.3. Advice for firefighters

Personal protective equipment	Self contained breathing apparatus and full protective clothing must be worn in case of fire.
Other information	Avoid breathing dust / fume / gas / mist / vapours / spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Provide adequate ventilation.
Protective equipment	Use personal protective equipment as required.

6.2. Environmental precautions

Environmental precautionary	Runoff or release to sewer, waterway or ground is forbidden. Prevent spillage
measures	entering a watercourse or sewer, contaminating soil or vegetation. If this is not
	possible notify police and appropriate authorities immediately.

6.3. Methods and material for containment and cleaning up

Clean up	Ventilate well. Dilute with copious amounts of water. Large Spillages: Remove spillage with vacuum cleaner. If not possible, collect spillage with shovel, broom or the like. Neutralise spilled material with crushed
	limestone, soda ash or lime. Shovel into dry containers. Cover and move the containers. Flush the area with water.

6.4. Reference to other sections

Other instructions For personal protection, see section 8.

For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling Provide sufficient air exchange and/or exhaust in work rooms.

Protective safety measures

clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Store in tightly closed original container in a dry, cool and well-ventilated place.

Conditions to avoid Avoid frost.

Conditions for safe storage

Packaging compatibilities Plastic. (PE, PP, PVC).

Plastic lined steel drum.

Titanium

glass fiber strenghtened poly ester

Storage temperature Value: > 0 < 30 °C

7.3. Specific end use(s)

Specific use(s) Water treatment material.

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Substance	Identification	Exposure limits	TWA Year
Polyaluminium chloride	CAS No.: 1327-41-9	Country of origin: Great	
		Britain	
		Limit value type: TWA	
		Limit value (8 h) : 2 mg/m³	
		Comments: EH40/2005	
		(Fourth Edition 2020)	

DNEL / PNEC

DNEL Group: Professional

Route of exposure: Long-term inhalation (systemic)

Value: 16,4 mg/m³

Group: Professional

Route of exposure: Long-term dermal (systemic)

Value: 4,6 mg/kg

Group: Consumer
Route of exposure: Long-term inhalation (systemic)
Value: 4 mg/m³

Group: Consumer
Route of exposure: Long-term dermal (systemic)
Value: 2,32 mg/kg bw/day

Group: Consumer
Route of exposure: Long-term oral (systemic)
Value: 2,3 mg/kg

PNEC

Comments: Not relevant.

8.2. Exposure controls

Precautionary measures to prevent exposure

Appropriate engineering controls	Provide adequate ventilation. Avoid contact with skin and eyes. Use personal protective equipment as required.
Product related measures to	Provide eyewash, quick drench.
prevent exposure	

Eye / face protection

Suitable eye protection	Wear approved chemical safety goggles where eye exposure is reasonably
	probable.

Hand protection

Skin- / hand protection, short term contact	Protective gloves must be used if there is a risk of direct contact or splash.
Suitable gloves type	Rubber gloves are recommended.
Suitable materials	Polyvinyl chloride (PVC). Neoprene.
Hand protection, comments	The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Skin protection

Suitable protective clothing	Wear appropriate clothing to prevent reasonably probable skin contact. Apron or other light protective clothing and boots.
Additional skin protection	Wear rubber footwear.
measures	

Respiratory protection

Respiratory protection, general	Under normal conditions of use respiration protection should not be required. In case of inadequate ventilation wear respiratory protection.
Respiratory protection necessary at	Avoid forming spray/aerosol mists.
Recommended type of equipment	Use respiratory equipment with particle filter, type P2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form Liquid

Physical state Liquid.

Colour Yellowish. Odour Not relevant.

рΗ Value: ~ 1.5 Melting point / melting range

Boiling point / boiling range Value: 100 - 120 °C

Flammability This product is not flammable.

Density Value: 1,28 - 1,34 g/cm3

Solubility Comments: Completely soluble in water.

Temperature: 20 °C

Value: - 30 °C

Partition coefficient: n-octanol/

water

Comments: Not applicable.

Decomposition temperature Value: > 200 °C

Viscosity Value: 10 - 30 mPa.s

Temperature: 23 °C

Explosive properties Not classified.

Oxidising properties None.

9.2. Other information

Other physical and chemical properties

Physical and chemical properties May be corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity May be corrosive to metals.

10.2. Chemical stability

Stability Stable under normal temperature conditions.

Thermal decomposition can take place above 200 °C.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Exothermic reaction with: Strong alkalis.

10.4. Conditions to avoid

Conditions to avoid Do not store near heat sources or exposed to high temperatures. Store above freezing.

10.5. Incompatible materials

Materials to avoid Metals.

Strong alkalis. Reducing Agents. sulphites Sulphides

Organic materials

10.6. Hazardous decomposition products

Hazardous decomposition

When heated, vapours/gases hazardous to health may be formed.

products

Hydrogen chloride (HCl). Sulphurous gases (SOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity Effect tested: LD50

Route of exposure: Oral Value: > 2000 mg/kg

Species: Rat

Effect tested: LC50

Route of exposure: Inhalation.

Value: > 5,0 mg/l Species: Rat

Effect tested: LD50

Route of exposure: Dermal Value: > 2000 mg/kg

Species: Rat

Other information regarding health hazards

Skin corrosion / irritation test

result

Method: OECD 404 Species: Rabbit

Evaluation result: Not Irritating. Comments: (45 % solution)

Skin corrosion / irritation, other

information

Prolonged and frequent contact may cause redness and irritation.

Eye damage or irritation, test

results

Method: OECD 405 Species: Rabbit

Evaluation result: Severe irritation.

Comments: (45 % liuos)

Eye damage or irritation other

information

Causes serious eye damage.

Sensitisation Not Sensitising.

Mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity, other information	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Assessment of specific target organ toxicity - single exposure, classification	Based on available data, the classification criteria are not met.
Assessment of specific target organ toxicity - repeated exposure, classification	Based on available data, the classification criteria are not met.
Aspiration hazard, comments	Based on available data, the classification criteria are not met.

Symptoms of exposure

In case of ingestion	Irritating. May cause nausea, stomach pain and vomiting.
In case of skin contact	May irritate and cause redness and pain.
In case of inhalation	May cause irritation to the respiratory system.
In case of eye contact	Irritating and may cause redness and pain. Causes serious eye damage.

11.2 Other information

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity, fish	Value: > 1000 mg/l Effect dose concentration: NOEC Exposure time: 96 hour(s) Species: Danio rerio (zebra fish) Method: OECD 203
Aquatic toxicity, algae	Value: 14 mg/l Effect dose concentration: EC50 Exposure time: 72 hour(s) Species: Pseudokirchneriella subcapitata (green algae) Value: 0,24 mg/l Effect dose concentration: EC50 Exposure time: 72 hour(s) Species: Pseudokirchneriella subcapitata (green algae) Method: OECD 201
	Comments: (AI)
Aquatic toxicity, crustacean	Value: 98 mg/l Effect dose concentration: EC50 Species: Daphnia magna Method: OECD 202

12.2. Persistence and degradability

Persistence and degradability	Not Applicable - Inorganic chemical.
description/evaluation	

12.3. Bioaccumulative potential

Bioaccumulation, comments

Bioaccumulation: Is not expected to be bioaccumulable. Not Applicable - Inorganic chemical.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB	This substance is not classified as PBT or vPvB.
assessment	

12.6. Endocrine disrupting properties

Endocrine disrupting properties None known.

12.7. Other adverse effects

Additional ecological information May lower the pH of water and thus be harmful to aquatic organisms. Runoff or release to sewer, waterway or ground is forbidden.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate methods of disposal for the chemical	Waste is classified as hazardous waste. Dispose of waste and residues in accordance with local authority requirements. Jäännökset laimennetaan vedellä ja neutraloidaan sitten kalkilla tai kalkkikivijauheella. Do not allow runoff to sewer, waterway or ground.
Appropriate methods of disposal for the contaminated packaging	Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: Transport information

Dangerous goods	Yes

14.1. UN number

ADR/RID/ADN	3264
IMDG	3264
ICAO/IATA	3264

14.2. UN proper shipping name

Proper shipping name English ADR/RID/ADN	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Technical name/Danger releasing substance English ADR/RID/ADN	(Polyaluminium chloride)
ADR/RID/ADN	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Technical name/danger releasing substance ADR/RID/ADN	(Polyalumiinikloridi)

IMDG	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Technical name/danger releasing substance IMDG	(Polyaluminium chloride)
ICAO/IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Technical name/danger releasing substance ICAO/IATA	(Polyaluminium chloride)

14.3. Transport hazard class(es)

ADR/RID/ADN	8
Classification code ADR/RID/ADN	C1
IMDG	8
ICAO/IATA	8

14.4. Packing group

ADR/RID/ADN	III
IMDG	III
ICAO/IATA	III

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

Additional information

Hazard label ADR/RID/ADN	8
Hazard label IMDG	8
Hazard label ICAO/IATA	8

ADR/RID Other information

Tunnel restriction code	E
Transport category	3
Hazard No.	80
Other applicable information ADR/RID	80

IMDG Other information

EmS	F-A. S-B

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

Assessed restrictions	Not known.
Legislation and regulations	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical safety assessment

Chemical safety assessment performed	Yes
CSR required	Yes

SECTION 16: Other information

SECTION 10. Other information	
Supplier's notes	The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.
List of relevant H-phrases (Section 2 and 3)	H290 May be corrosive to metals. H318 Causes serious eye damage.
CLP classification, notes	The information provided is based on data on ingredients.
Key literature references and sources for data	Manufacturers material safety data sheet 12.04.2021
Information added, deleted or revised	Relevant changes compared to the previous version of the safety data sheet are indicated with verticle lines in the left margin.
Version	1