

IP20

IP67



LIITÄNTÄLAITTEET JA HIMMENNINYKSIKÖT



4016021 TASAJÄNNITELÄHDE 12V 6W IP20

Muovikotelo
SELV 12V 6W, 50–60Hz
50 000 h
-15 ... 45 °C
77 x 43 x 23 mm, 0,04 kg
Päättyvä.



4016001 TASAJÄNNITELÄHDE 12V 100W IP20

Muovikotelo
SELV 12V 100W, 50–60Hz
50 000 h
-15 ... 45 °C
290 x 40 x 30 mm, 0,45 kg
Ketjutettava.



4016020 TASAJÄNNITELÄHDE 12V 20W IP20

Muovikotelo
SELV 12V 20W, 50–60Hz
50 000 h
-15 ... 45 °C
118 x 45 x 19 mm, 0,13 kg
Ketjutettava.



4289780 LED DRIVER 60W OTP IP67

Metallirunko, IP67
SELV 12V 60W, 50–60Hz
50 000 h
-25 ... 55 °C
180 x 50 x 34 mm, 0,7 kg
Kytkenä erillisessä rasiassa.



4016019 TASAJÄNNITELÄHDE 12V 30W IP20

Muovikotelo
SELV 12V 30W, 50–60Hz
50 000 h
-15 ... 45 °C
162 x 41 x 32 mm, 0,25 kg
Ketjutettava.



4289782 LED DRIVER 120W OTP IP67

Metallirunko, IP67
SELV 12V 120W, 50–60Hz
50 000 h
-25 ... 55 °C
250 x 60 x 39 mm, 1,15 kg
Kytkenä erillisessä rasiassa.



4016018 TASAJÄNNITELÄHDE 12V 60W IP20

Muovikotelo
SELV 12V 60W, 50–60Hz
50 000 h
-15 ... 45 °C
170 x 52 x 30 mm, 0,35 kg
Ketjutettava.



4016022 HIM.YKS. IP20 12V/24V DALI/PUSH DIM

Muovikotelo
SELV 12V/100W, 24V/200W, 50–60Hz
50 000 h
-5 ... 35 °C
145 x 47 x 16 mm, 0,12 kg
Päättyvä.