

Painoväli K/K tarkoittaa mittaa painon keskeltä seuraavan painon keskelle

40mm PN10 PE100	80% K/K 3,16m	100% K/K 2,52m	120% K/K 2,10m
40mm PN16 PE100	80% K/K 3,58m	100% K/K 2,86m	120% K/K 2,38m
50mm PN10 PE100	80% K/K 2,06m	100% K/K 1,65m	120% K/K 1,37m
50mm PN16 PE100	80% K/K 2,33m	100% K/K 1,86m	120% K/K 1,55m
63mm PN10 PE100	80% K/K 1,19m	100% K/K 0,95m	120% K/K 0,79m
63mm PN16 PE100	80% K/K 1,38m	100% K/K 1,11m	120% K/K 0,92m
75mm PN10 PE100	80% K/K 1,84m	100% K/K 1,47m	120% K/K 1,22m
75mm PN16 PE100	80% K/K 2,12m	100% K/K 1,70m	120% K/K 1,42m
110mm PN10 PE100	80% K/K 2,46m	100% K/K 1,96m	120% K/K 1,64m
110mm PN16 PE100	80% K/K 2,84m	100% K/K 2,27m	120% K/K 1,89m
140mm PN10 PE100	80% K/K 2,12m	100% K/K 1,69m	120% K/K 1,41m
140mm PN16 PE100	80% K/K 2,44m	100% K/K 1,95m	120% K/K 1,62m
160mm PN10 PE100	80% K/K 2,53m	100% K/K 2,03m	120% K/K 1,69m
160mm PN16 PE100	80% K/K 2,93m	100% K/K 2,35m	120% K/K 1,95m