



## CRC EXHAUST REPAIR GUM

Ref. : 10555

### 1. GENERAL DESCRIPTION

---

Repair putty for exhaust systems.

A black putty formulated with inorganic binders, fibres, additives and water. Exhaust Repair Gum repairs small holes and cracks in exhaust systems without welding or disassembling.

### 2. FEATURES

---

- Hardens completely by an overnight dry or a 10 min. idling.
- Dry product ensures gas-tight repairs.
- Reduces lasting noise.
- Easily applied by hand or with a putty knife.
- For hard to reach areas and for a smooth finish, the product can be softened with some water.
- Asbestos- and solvent-free.
- Withstands heat, water and vibrations after hardening.
- Presented in a tin for easy access and application.

### 3. APPLICATIONS

---

- Exhaust pipes
- Silencers
- Expansion boxes

### 4. DIRECTIONS

---

- Clean repair area and remove loose rust.
- Moisten repair area with water.
- Apply Gum by hand or with a putty knife. Force gum well into the hole. Smoothen surface with wet hand or putty knife.
- Leave to harden for approximately 12 hours. Hardening can be accelerated by idling the engine for about 10 minutes.
- When required, Exhaust Repair Gum can be softened by adding some water.
- For larger holes, use CRC Exhaust Bandage.
- Close tin well after use to prevent product from setting in the tin.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
www.crcind.com





## CRC EXHAUST REPAIR GUM

Ref. : 10555

### 5. TYPICAL PRODUCT DATA (without propellant)

---

Appearance	: black putty
Specific gravity @ 20°C	: 1.85
Flash point	: not flammable
pH	: 10
Solids content (6 h @ 100°C)	: 76 % wt
Maximum use temperature	: 1000°C

### 6. PACKAGING

---

tin : 12 x 200 g

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com).

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10555 03 0197 01  
Date : 23 september 2003



Manufactured by :  
CRC Industries Europe NV  
Touwslagerstraat 1 – 9240 Zele – Belgium  
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)

